

Recent Advances in Thermal Management Techniques for High-Performance PMSMs - A Comprehensive review

Md Ali Azoma^{1,*}, Md Yakub Ali Khan²

^{1,*} Department of Mechanical and Power Engineering, Nanjing Tech University, China

² Department of Electrical and Electronic Engineering, World University of Bangladesh, Uttara, Dhaka Bangladesh

¹ aliajom786@gmail.com, ² yakub.bimt@gmail.com

*Corresponding Author

Abstract—This paper presents recent advancements in thermal management techniques for high-performance permanent magnet synchronous motors (PMSMs), highlighting their role in improving efficiency and reliability. Due to their high-power density, small size, and exceptional efficiency, permanent magnet synchronous motors, or PMSMs, have become indispensable in high-performance applications like industrial automation, electric cars, and aerospace. Since excessive heat generation can lower motor efficiency, shorten its lifespan, and jeopardize dependability, the growing demands for improved performance have created serious issues in thermal management. The latest developments in thermal management strategies for high-performance PMSMs are thoroughly examined in this paper. Important thermal issues are covered, such as the development of hot spots, unequal heat distribution, and thermal resistance at crucial contacts. The incorporation of cutting-edge cooling technologies into motor design is examined in this research, along with liquid cooling, heat pipes, phase change materials, and enhanced thermal interface materials. Furthermore, it is emphasized how important computational thermal modeling and simulation are to maximizing PMSM thermal performance. The interaction of mechanical, thermal, and electrical dynamics is emphasized to provide dependable and effective motor operation. This review identifies current limitations and explores future trends, including adaptive cooling techniques and AI-driven thermal modeling, to enhance PMSM efficiency and sustainability. This will allow for further breakthroughs in sustainable and energy-efficient technologies.

Keywords—Advances; Thermal Management; Techniques; Performance; PMSM; Material Innovations

I. INTRODUCTION

A class of electric motors and generators known as Permanent Magnet Synchronous Machines (PMSMs) generate a magnetic field without the usage of external stimulation by using permanent magnets integrated in the rotor. Modern applications make extensive use of PMSMs because of their great efficiency, small size, and accurate control. In contrast to induction machines, PMSMs continue to operate in synchrony with the frequency of the supplied current, guaranteeing steady performance under a range of load scenarios [1]. PMSMs are structurally composed of a rotor embedded with high-strength permanent magnets, which are frequently comprised of rare-earth elements like neodymium-iron-boron (NdFeB), and a stator with a three-phase winding. By lowering losses related to current-induced magnetism, these magnets improve energy efficiency by

producing a steady magnetic field. PMSMs work by creating torque through the interaction of the rotor's magnetic field and the stator's revolving magnetic field [2]. Eliminating brushes and sliding rings improves dependability, lowers maintenance requirements, and permits quieter operation. High-performance applications including robots, electric cars, aerospace systems, and renewable energy production are especially well-suited for PMSMs. They are perfect for precise control because of their exceptional torque density, high power-to-weight ratio, and better dynamic response. Furthermore, their operational capabilities have been greatly improved by developments in power electronics and control algorithms, such as field-oriented control (FOC) [3]. Notwithstanding its advantages, issues including demagnetization dangers, rare-earth material costs, and thermal control need to be resolved for wider usage across a range of industries. Permanent Magnet Synchronous Motors (PMSMs) have many benefits, but they also have a number of drawbacks that affect their long-term dependability and effectiveness. One significant worry is the possibility of demagnetization, in which the permanent magnets may become weaker due to high temperatures or excessive currents, resulting in a decline in performance. Furthermore, PMSMs are expensive to create due to their reliance on rare-earth elements like dysprosium and neodymium, which are similarly vulnerable to supply chain restrictions. Thermal management is another crucial concern since too much heat accumulation can harm the insulation and magnets, lowering their lifespan and efficiency. Innovative solutions are needed to address these issues, such as better cooling methods, substitute magnet materials, and improvements in motor design that increase longevity and economy.

For high-performance permanent magnet synchronous motors (PMSMs) to operate at their best and be reliable, thermal control is crucial. Elevated iron losses, higher stator winding resistance, and demagnetization of permanent magnets are all consequences of high temperatures that lower torque output and efficiency. Furthermore, overheating can limit the motor's lifespan, harm bearings, and deteriorate insulation. Because too much heat can result in irreversible losses in magnetic characteristics, permanent magnets are especially susceptible to thermal instability. Because unchecked heat accumulation can lead to component failure and operational dangers, effective thermal management is also essential for safety. Real-time thermal monitoring, active

cooling, and passive cooling are some of the tactics used to overcome these obstacles. Effective thermal management is essential for applications in electric vehicles, renewable energy systems, and industrial automation because it enables PMSMs to function closer to their performance limits without sacrificing durability.

This review critically examines recent advancements in PMSM thermal management, identifying key challenges, emerging solutions, and their implications for high-performance applications. It seeks to draw attention to how important good thermal management is for improving motor performance, efficiency, dependability, and safety, especially in challenging working environments. In addition, the review examines how thermal stress affects motor parts like winding insulation and permanent magnets and assesses several cooling strategies, such as passive and active systems. With an emphasis on their suitability for high-performance applications like electric vehicles, renewable energy systems, and industrial automation, the coverage includes recent advancements in thermal management technologies, material improvements, and design optimizations. The paper aims to give researchers and engineers useful information for creating reliable thermal management systems for next-generation PMSMs by addressing these factors.

II. THERMAL CHALLENGES IN PMSMS

The interplay of electrical, magnetic, and mechanical components during operation is the main cause of heat generation in permanent magnet synchronous motors (PMSMs), however there are other sources as well.

A. Copper Losses (I^2R Losses)

As current passes through the stator windings, the resistance causes copper losses, producing heat proportional to I^2R , where I represent current and R is the resistance. Because resistance increases with temperature, these losses are made worse by high operating temperatures and increase with larger current demands.

B. Iron Losses (Hysteresis and Eddy Current Losses)

Because the core material repeatedly undergoes magnetization and demagnetization throughout each electrical cycle. arising from circulation currents that time-varying magnetic fields create in the core. The size and frequency of the flux density determine these losses. As the magnetic field continuously shifts direction, the core material repeatedly magnetizes and demagnetizes, resulting in hysteresis losses. The internal friction of the magnetic domains realigning causes some of the energy to be lost as heat each time the material goes through this cycle. The frequency of magnetic reversals, the kind of core material, and the area of its hysteresis loop all affect these losses. Engineers frequently employ materials with short hysteresis loops, like silicon steel or specialty soft magnetic alloys, to reduce hysteresis losses. These materials enhance overall efficiency in electrical machines and transformers by requiring less energy for magnetization reversal.

C. Permanent Magnet Losses

When subjected to high-frequency harmonics in the magnetic field, permanent magnets may suffer eddy current losses, especially in high-speed motors or those with intricate

control schemes. Magnet performance and efficiency are decreased by this heat buildup.

D. Impact of Thermal Issues on Motor Performance and Reliability

Permanent magnet synchronous motors' (PMSMs) dependability and performance are greatly impacted by thermal problems. Overheating can cause permanent magnets to demagnetize, which lowers the torque production and efficiency of the motor. Higher temperatures cause stator winding resistance to increase, which raises copper losses and reduces energy efficiency. Furthermore, thermal stress quickens the deterioration of winding insulation, which shortens motor lifespan and causes electrical failures. Heat also affects bearings and other mechanical parts because thermal expansion can lead to misalignments and increased wear, which can jeopardize the dependability of the motor. High temperatures further worsen eddy current and iron losses, which further reduces performance. These problems, especially in high-demand applications like industrial systems and electric cars, can lead to frequent maintenance, unplanned breakdowns, and decreased operating safety in the absence of efficient heat management. Therefore, addressing temperature issues is crucial to ensuring PMSMs' long-term performance, effectiveness, and durability [4].

E. Critical Need for Efficient Thermal Management in High-Performance Applications (e.g., EVs, Aerospace, and Robotics)

In high-performance applications like robotics, aerospace systems, and electric vehicles (EVs), where permanent magnet synchronous motors (PMSMs) are extensively utilized, effective temperature management is vital. These applications generate a lot of heat because they require compact designs, high power densities, and extended operation in harsh environments. Ineffective thermal management can cause problems including insulation failure, magnet demagnetization, and higher losses, which can impair PMSM performance and dependability and eventually result in inefficiencies and possible system failures [5]. Inadequate cooling in EVs can impair safety, impact acceleration, and shorten driving range. Similarly, overheating can endanger mission performance in aircraft applications where thermal and weight limits are crucial. Overheating in robotics can reduce accuracy, speed, and lifespan. Effective thermal management, achieved through sophisticated cooling methods and thermal monitoring, guarantees the best possible motor performance, increases longevity, and satisfies the demanding requirements of these state-of-the-art technologies [6].

III. THERMAL MODELLING OF PMSMS

A mathematical technique called analytical thermal modeling is used to forecast the heat flow and temperature distribution inside permanent magnet synchronous motors (PMSMs). It entails breaking down the motor's intricate architecture and thermal behavior into a simple set of equations using the concepts of heat transfer [7]. Typically, the model takes into consideration heat dissipation processes like conduction, convection, and radiation as well as heat generating sources including copper losses, iron losses, and eddy current losses. The stator, rotor, air gap, winding, and

other discrete areas of the motor are each handled as independent thermal domains with unique characteristics. Temperature gradients are computed by solving steady-state or transient heat conduction equations. To take into consideration ambient heat transfer or external cooling, convective and radiative boundary conditions are used [8]. Every part of the motor such as the windings, magnets, and core are modeled as a thermal resistor in order to depict the motor as a thermal resistance network. Electrical circuit analogies are then used to compute the heat flow through the system. As input heat sources in the model, losses from copper, iron, and magnets are calculated according to motor operating parameters. To guarantee precise forecasts, motor materials' thermal conductivity, specific heat, and emissivity are considered [9].

A potent computational method for modeling and analyzing the heat distribution and thermal behavior of permanent magnet synchronous motors (PMSMs) is finite element analysis (FEA) for thermal simulations. By breaking the motor down into tiny, distinct components, FEA, as opposed to analytical models, enables a thorough, spatially resolved analysis of temperature fluctuations. More precise simulation of intricate geometries and material properties is made possible by treating each element as a thermal unit with unique heat conduction, convection, and radiation capabilities. Both transient and steady-state heat flow, as well as the effects of changing operating conditions, thermal loads, and losses in parts like the stator, rotor, magnets, and bearings, can be taken into consideration by FEA [10]. It is especially helpful for pinpointing hot places, evaluating how cooling systems work, and refining motor designs for better thermal performance. Because of its high degree of accuracy, FEA is perfect for forecasting how motors will behave in real-world scenarios and making sure that thermal limits are not exceeded. This is crucial for guaranteeing motor longevity, efficiency, and dependability, particularly in high-performance applications like robotics, electric cars, and aerospace [11].

The lumped parameter a simplified modeling technique called thermal networks (LPTN) is used to examine thermal behavior and heat transport in systems like permanent magnet synchronous motors (PMSMs) [12]. Each component, including the stator, rotor, and bearings, is regarded as a single thermal mass with a constant temperature in an LPTN, which represents the motor as a network of thermal resistances and capacitances. Thermal capacitances, which take into consideration each component's capacity to store heat, and thermal resistances, which depict heat transfer between them, are what bind these parts together. Although LPTN models are computationally efficient and appropriate for real-time thermal analysis since they presume that temperature gradients within each component are minimal, they do not forecast temperature variations inside the components with the same level of accuracy [13]. Because it can rapidly estimate a motor's entire thermal response to various operating situations, including transient heat generation from losses and the impact of external cooling systems, the LPTN technique is very helpful for system-level thermal management. For early-stage design and optimization, LPTN provides a useful and effective solution, even if it is less comprehensive than more sophisticated

techniques like finite element analysis (FEA). This is particularly true when working with big systems or when real-time performance monitoring is necessary [14].

There are two methods for examining the thermal behavior of systems such as permanent magnet synchronous motors (PMSMs): transient and steady-state thermal modeling. Each has a specific function. According to steady-state thermal modeling, the motor's internal temperature has stabilized, indicating that heat generation and dissipation are balanced and that there aren't any notable variations over time. Insights into the motor's temperature distribution after it has achieved thermal equilibrium are provided by this kind of simulation, which is used to assess long-term operating conditions under steady workloads [15]. Steady-state models are perfect for evaluating performance under typical operating settings and making sure the motor maintains below acceptable temperature limits because they are easier to understand and more computationally efficient. In order to analyze and optimize permanent magnet synchronous motors (PMSMs), co-simulation techniques that combine electrical and thermal models are becoming more and more crucial [16]. These methods combine the thermal model, which computes heat generation, temperature distribution, and thermal impacts, with the electrical model, which models the motor's electrical dynamics, including current, voltage, and electromagnetic forces. Co-simulation enables a more realistic depiction of the motor's behavior under actual operating settings by tying these two domains together. For instance, the thermal model can forecast how these losses would impact the motor's temperature over time, while the electrical model can give real-time information on the heat-generating losses in the rotor and stator [17].

IV. ADVANCED COLLING TECHNIQUES

One of the most popular advanced cooling methods for permanent magnet synchronous motors (PMSMs) is air-cooling, especially in applications where affordability, ease of use, and modest cooling are critical. Airflow, either natural or induced, dissipates heat from the motor components in air-cooling systems [18]. By improving convective cooling, forced air-cooling which involves using a fan or blower to drive air over the motor's surface increases the rate of heat transfer. This technique helps maintain a constant temperature and avoid overheating, making it effective for motors running at moderate to high loads. To improve surface area and encourage more effective heat dissipation, fins or heat sinks are frequently incorporated into the motor casing design. Although air-cooling is very simple to set up and doesn't require complicated equipment, environmental factors like airflow constraints and ambient temperature limit how efficient it is. In high-performance applications, such as robots or electric cars, where motors must function under harsh circumstances, air cooling can be used in conjunction with other methods, like liquid cooling, to improve heat removal and preserve ideal operating temperatures [19]. For many PMSMs, air-cooling is still a crucial and popular cooling technique, despite its drawbacks in harsh conditions.

A. Air-Cooling

A passive cooling method called natural convection cooling uses the air or fluid's inherent flow to remove heat from the permanent magnet synchronous motors' (PMSMs')

surface [20]. A constant flow of air surrounds the motor as a result of the heat produced by the motor's parts warming, densifying, and rising the surrounding air and replacing it with cooler air. Without the need of mechanical fans or pumps, this natural circulation aids in the removal of heat. Applications that prioritize simplicity, low maintenance, and energy efficiency, as well as those with mild cooling requirements, are usually best suited for natural convection [21].

Using mechanical fans or blowers to actively direct airflow over the motor's surfaces, forced air-cooling with optimal flow designs is a cutting-edge cooling approach that improves heat dissipation in permanent magnet synchronous motors (PMSMs). This technique pushes air into the motor's cooling tubes, windings, and other vital parts, greatly increasing the rate of heat transfer when compared to natural convection [22]. By improving the flow design, such as by strategically placing cooling fins, heat sinks, and vents to maximize the surface area available for heat exchange, the efficiency of forced air cooling can be further increased. Airflow patterns are frequently improved by using computational fluid dynamics (CFD) simulations, which guarantee that hot regions inside the motor are efficiently cooled. Furthermore, by reducing turbulence and guaranteeing that cold air reaches every component of the motor, well-designed ducts and airflow channels can increase overall efficiency. High-performance PMSMs used in robotics, industrial machines, and electric vehicle applications where motors must function under harsh conditions benefit greatly from forced air cooling with optimized flow designs [23]. This cooling strategy helps preserve motor performance, avoid overheating, and increase motor life by effectively controlling the heat produced during heavy loads or abrupt changes in operating conditions.

Due to the higher heat generation and restricted heat dissipation capacity of air, air cooling in high-power-density machines like permanent magnet synchronous motors (PMSMs) used in electric vehicles or industrial applications present several difficulties [24]. The quantity of heat generated per unit rises with power density, which, if not controlled, might overwhelm the cooling system. Inadequate cooling capacity is a major issue since air's comparatively low thermal conductivity makes it difficult for high-performance motors to efficiently remove heat, particularly during times of high-power output or abrupt shifts. Heat accumulation can result in hotspots in vital motor parts, like the stator windings and magnets, which can lower efficiency, increase losses, and perhaps cause permanent magnet demagnetization or damage to insulation [25].

Uneven airflow distribution is another issue; high-power-density machines frequently have intricate geometries, making it challenging to guarantee that air reaches all vital motor components. Localized heating caused by inadequate airflow dispersion can be especially troublesome in smaller, densely packed motors [26]. Additionally, the effectiveness of forced air-cooling systems may be diminished by the size limitations of cooling ducts and fans in compact, high-power-density designs. Another limiting element is ambient temperature; a hotter environment will make the air less efficient at cooling, increasing the system's susceptibility to overheating. High-speed fans or blowers are frequently

needed to generate the required airflow, which can raise operating noise and energy consumption. Lastly, noise and energy consumption can become issues in forced air-cooling systems. Air cooling is frequently employed in conjunction with other techniques, like liquid cooling or phase-change materials, to overcome these difficulties. In high-power-density machines, heat dissipation is improved through sophisticated flow designs and heat sink optimization [27].

B. Liquid Cooling

High-performance permanent magnet synchronous motors (PMSMs), especially those employed in applications requiring high power densities, such as industrial systems or electric vehicles, can effectively manage heat using liquid cooling techniques like jacket cooling. A coolant, usually water or a water-glycol mixture, travels through a cooling jacket that encircles the motor, usually around the stator or other important parts, in jacket cooling. This jacket effectively absorbs and removes heat from the motor by ensuring a steady flow of coolant across its surface. To remove heat from motor components like the stator or rotor, a tiny mist of coolant, usually water or oil, is sprayed directly onto their hot surfaces. This is known as direct oil or water spray cooling. This technique works especially well in high-power-density applications where managing the significant amounts of heat produced during operation may be beyond the capabilities of conventional cooling techniques. Heat is quickly absorbed from the motor surfaces by the coolant, which is a thin spray, and then evaporates, removing the heat as vapor. By increasing the coolant's surface area in contact with the heated surfaces, this method can effectively dissipate heat. An inventive method that improves the thermal management of permanent magnet synchronous motors (PMSMs), especially in high-performance applications, is the use of dielectric fluids in liquid cooling systems. Because they don't conduct electricity, dielectric fluids like synthetic oils or specially made non-conductive fluids are safe to employ when cooling delicate electrical components. These fluids are commonly utilized in cooling systems that must cool the motor's electrical components such as the power electronics and stator windings without running the danger of electrical failure or short circuits.

C. Phase Change Materials (PCM)

Phase change materials (PCMs) efficiently absorb and store surplus heat, which helps to improve the thermal management of high-performance systems, such as permanent magnet synchronous motors (PMSMs). During the phase transition from solid to liquid or from liquid to gas at a particular temperature, referred to as the melting or boiling point, PCMs use their capacity to absorb heat. PCMs offer a highly effective means of heat absorption because of this phase shift, which enables them to store enormous amounts of thermal energy without experiencing a noticeable increase in temperature. A novel approach to improving heat management in high-performance systems like permanent magnet synchronous motors (PMSMs) is the use of phase change materials (PCMs) into motor designs. PCMs are positioned deliberately where considerable heat generation takes place, usually near important motor parts like the housing, rotor, or stator windings. A PCM with a melting point that corresponds to the motor's operational temperature

range must be chosen as part of the integration procedure. Typically, PCM is integrated into the motor design as either encapsulated packets or directly into the heat sinks, cooling jackets, or motor casing.

Even though phase change materials (PCMs) provide high-performance systems like permanent magnet synchronous motors (PMSMs) with substantial advantages in thermal control, their successful application requires overcoming a number of obstacles. Heat transmission efficiency is one of the main obstacles. Despite being efficient in absorbing and holding heat during their phase transition, PCMs frequently have low thermal conductivity, which can restrict how quickly heat is absorbed or released. To get around this, PCMs need to be combined with substances that improve their thermal conductivity, like metal matrices or ultra-conductive additives, which can speed up heat transmission.

D. Heat Pipes and Vapor Chambers

Advanced thermal management tools like vapor chambers and heat pipes effectively transport heat by applying the concepts of phase transition. A heat pipe is a passive, sealed device that transfers heat from a heated region to a colder one by evaporating and condensing a working fluid. A significant amount of heat is absorbed by the working fluid when it evaporates when heat is applied to one end of the heat pipe. After passing through the pipe to the cooler end, the vapor releases the heat it has absorbed by condensing back into a liquid. By capillary action, gravity, or some other mechanism, the liquid completes the cycle by returning to the hot end. Although they are flat, two-dimensional devices made to distribute heat uniformly across a surface, vapor chambers work on a similar basis. The fluid evaporates as a result of the heat being absorbed at a particular location, and the vapor is subsequently dispersed throughout the chamber, thus dispersing the heat over a greater region. Power electronics, motors, and high-performance systems that need small and efficient cooling solutions frequently use heat pipes and vapor chambers because they are both very good at controlling thermal loads and provide effective heat dissipation without causing appreciable temperature increases [28].

E. Emerging Techniques

Jet impingement cooling is an emerging thermal management technique that involves directing a high-velocity jet of fluid, usually air or liquid, onto the surface of a hot object, such as a motor component, to enhance heat dissipation. The high-speed jet impacts the surface, creating turbulence that increases the heat transfer coefficient and facilitates more effective cooling. The primary advantage of jet impingement is its ability to provide localized and intense cooling, making it particularly suitable for high-heat flux applications such as high-performance motors, electronics, and power systems [29].

The suspension of nanoparticles, usually composed of metals, oxides, or carbon-based compounds, in a base fluid, like water or oil, is known as Nano fluids, and it is a new method in liquid cooling. These nanoparticles improve the fluid's thermal characteristics, such as its thermal conductivity and rate of heat transfer, which makes Nano fluids ideal for cooling high-performance devices including

industrial machinery, power electronics, and motors [30]. A very effective coolant that can absorb and transfer heat more efficiently than traditional fluids is produced by adding nanoparticles to the fluid. This is because nanoparticles have a large surface area, which enhances heat transfer by boosting fluid-heat source interaction.

An inventive method of cooling high-performance systems and gadgets, like motors, power electronics, and heat-sensitive machinery, is represented by 3D-printed thermal management systems. These technologies enable the development of intricate, personalized cooling structures that are tailored to certain thermal requirements through the use of additive manufacturing. Complex cooling channels, heat sinks, and heat exchangers that would be challenging or impossible to construct using conventional techniques can now be designed thanks to 3D printing. By precisely matching the shape of the heat source, these structures can be designed to increase heat transmission, enhance airflow, and assure effective heat dissipation [31].

A developing method that actively modifies cooling levels in response to shifting thermal conditions is active thermal control with adaptive cooling systems. These systems employ sensors and feedback mechanisms to continuously check the temperature of vital parts, including power electronics or motors, and adjust or start cooling procedures in response to real-time data [32]. Variable-speed fans, pumps, or electrically controlled cooling channels are a few examples of adaptive cooling systems that can be used to modify their operation to boost or decrease heat dissipation as necessary. During times of high thermal load or when the system operates under variable conditions, this capacity to adjust to thermal fluctuations helps maintain maximum performance and avoid overheating [33].

V. MATERIAL INNOVATIONS FOR THERMAL MANAGEMENT

To increase the thermal performance and efficiency of permanent magnet synchronous motors (PMSMs) and other high-performance electric machines, high thermal conductivity materials for the stator and rotor cores are crucial. Important parts that produce and release a lot of heat when a motor is operating are the stator and rotor. High thermal conductivity materials, such copper, aluminum, or sophisticated composites, help to quickly transfer heat away from these parts, avoiding overheating and guaranteeing steady motor operation [34]. Because of its exceptional thermal and electrical conductivity, which promotes effective electrical current flow and heat dissipation, copper in particular is frequently utilized in stator windings. Furthermore, several high-conductivity composites which blend metals with ceramics or polymers are being investigated to offer a balance between mechanical strength and thermal conductivity, enhancing the motor's overall longevity and efficiency. The motor's temperature rise can be better managed by employing these high thermal conductivity materials, which lowers the possibility of damaging magnets, insulation, or other delicate parts. This is especially critical in high-power-density applications, like electric cars, where efficient heat management is essential to preserving performance and prolonging motor life. Cost, weight, mechanical characteristics, and compatibility with

other motor parts are some of the variables that affect the choice of the best material [35].

A viable strategy for enhancing thermal management in high-performance systems including electronics, power generation equipment, and permanent magnet synchronous motors (PMSMs) is the use of advanced composites for thermal insulation and conduction. By combining materials with varying thermal characteristics, these composites provide a balance between conduction and heat insulation that is suited to the needs of certain applications. Advanced composites, for example, can combine fibers, polymers, and ceramics to produce lightweight, thermally conductive materials that, when needed, also offer great thermal resistance [36]. These composites can be utilized in motor applications in parts such as housing, rotor cores, and stator windings to improve heat dissipation or offer insulation in areas where there is a high risk of overheating. While thermally insulating composites can stop undesired heat transfer and shield delicate components like magnets or electronics from extreme temperatures, thermal conductive composites can aid in the rapid transfer of heat from high-heat flux areas to cooler regions, increasing cooling efficiency. These materials are perfect for use in industrial, automotive, and aerospace machinery because they can be developed to fulfill specific design requirements including mechanical strength, weight reduction, and environmental resistance.

The performance and dependability of electric machines that operate under high thermal loads, such as permanent magnet synchronous motors (PMSMs), depend heavily on thermal enhancement in winding insulating materials. Usually composed of fibers, polymers, and resins, winding insulation materials are intended to prevent heat deterioration and shield the wind from electrical shorts. Their resistance to heat, however, is a drawback because high temperatures can degrade insulation, which might result in motor failure or a shorter lifespan. Advanced thermal enhancement techniques are being used to improve the heat resistance and thermal conductivity of insulating materials to overcome this issue.

To improve the thermal management of high-performance systems, such as motors, power electronics, and other heat-sensitive components, advanced cooling channel materials are essential. These materials are specifically made to maximize coolant flow, enhance heat transfer, and guarantee effective dissipation of heat produced during operation. Because of their distinct thermal characteristics, metals, composites, and polymers are often utilized materials for cooling channels. Because of their superior thermal conductivity, which enables effective heat transmission from the heat-generating components to the cooling medium, metals including copper, aluminum, and stainless steel are preferred alternatives [37]. Because it permits heat to move swiftly throughout the channel, copper in particular works very well in applications that call for speedy heat dissipation. Aluminum is frequently chosen when weight is an issue because of its favorable thermal characteristics and reduced weight. Another new material for cooling channels is advanced composites, which combine mechanical strength, excellent heat conductivity, and customized design flexibility. Metal matrices or ceramic fillers, which increase heat transmission and strengthen the material's resistance to

corrosion and high-temperature deterioration, may be incorporated into these composites. The efficiency of heat transfer can be further increased by using composites to enable more intricate and optimal channel designs, such as micro channels or porous structures.

VI. THERMAL MANAGEMENT IN SPECIFIC APPLICATIONS

For electric vehicle (EV) traction motors to operate at their best and last a long time, thermal management is essential. Effective thermal techniques are required to manage the heat produced by the motor during acceleration, braking, and continuous operation because EVs run under a variety of load circumstances and temperatures. One of the most popular methods for controlling heat in EV traction motors is liquid cooling. To absorb and eliminate extra heat, a coolant usually a water-glycol mixture is circulated through cooling jackets or channels surrounding the engine. After absorbing the heat from the motor's rotor and stator, the coolant transfers it to a radiator or heat exchanger for dissipation. This technique works well for avoiding overheating and keeping a constant motor temperature, particularly in high-performance or high-power-density motors [28]. These thermal strategies, often used in combination, help ensure that EV traction motors operate within the optimal temperature range, improving motor efficiency, performance, and reliability, while also extending the lifespan of key components. As EV technology advances and motors become more powerful and compact, the need for advanced and integrated thermal management systems will continue to grow.

Aerospace permanent magnet synchronous motors (PMSMs) face unique challenges due to the high thermal loads generated during operation, coupled with stringent weight constraints. The motors are crucial in various aerospace applications, including electric propulsion systems, actuators, and more, where efficiency, reliability, and performance are paramount. However, the high thermal loads created by the PMSM's electrical and mechanical power conversion processes require effective thermal management to ensure optimal motor operation and prevent overheating. PMSMs work at high power densities, which produce a lot of heat in comparatively tiny volumes, in aeronautical applications [38]. It is challenging to integrate conventional cooling techniques like big radiators or heavy heat exchangers because lightweight and compact motor designs are required. Additionally, PMSMs used in aerospace frequently function in a variety of temperature ranges, ranging from the bitterly cold high-altitude environments to the scorching heat during rapid acceleration or continuous high-speed operation. Controlling this temperature fluctuation is crucial for preserving the motor's longevity, preventing thermal damage to delicate parts (such the permanent magnets and windings), and preserving its efficiency.

Permanent magnet synchronous motors (PMSMs) are being used more and more in industrial and renewable energy applications because of their high efficiency, small size, and superior performance in a variety of operating circumstances. Wind turbines, solar energy systems, pumps, and manufacturing equipment are just a few of the many systems

that depend on these motors. However, to guarantee optimum performance, dependability, and longevity, PMSMs in these industries must have efficient heat management. Because of their accuracy, dependability, and high power-to-weight ratio, PMSMs are extensively utilized in manufacturing equipment, robotics, conveyor systems, HVAC systems, and industrial automation. The motors in these applications frequently operate at constant high-power levels while being subjected to a range of loads, speeds, and duty cycles. Controlling the motor's thermal loads is crucial to avoiding overheating, which can impair performance, harm insulation, or result in the failure of important parts. Because of their high torque density and capacity to function effectively throughout a broad range of rotational speeds, PMSMs are frequently employed in wind power generation. By removing the requirement for a gearbox, these motors are incorporated into direct-drive systems, increasing system reliability and lowering mechanical losses. However, PMSMs in wind turbines must constantly operate at different loads while being subjected to severe external conditions. To avoid overheating and guarantee long-term dependability, effective cooling systems such as liquid cooling, direct oil cooling, or even sophisticated hybrid systems employing heat pipes are crucial.

VII. CASE STUDIES

Liquid cooling systems are frequently used for PMSMs that operate in high-power-density situations, such as traction motors for electric vehicles (EVs). A coolant, usually a water-glycol mixture, flows through cooling channels built into the stator or rotor core in this configuration. Through a heat exchanger, the coolant removes the heat produced by the motor while it is operating [39]. In high-performance applications like electric vehicles and aircraft, where effective heat dissipation is crucial to preserving high motor efficiency and avoiding overheating, this technique is frequently employed. For example, liquid-cooled PMSMs are used by many EV manufacturers, including Tesla, to control the motor's temperature and improve performance. Heat pipes and vapor chambers are included into PMSM designs to passively regulate heat in applications where weight and space are crucial, like in portable machinery or aerospace. Heat pipes move heat from hotter locations to colder ones by allowing a working fluid to evaporate and condense [40].

Understanding how thermal control affects motor efficiency, longevity, and overall reliability requires comparing the performance of permanent magnet synchronous motors (PMSMs) before and after thermal management strategies are used. Engineering professionals can evaluate changes in a number of operational metrics, including temperature stability, power output, and system efficiency, by comparing the motor's performance under various thermal management techniques. The heat produced by electrical losses (such as copper losses in windings and core losses in the stator and rotor) can cause PMSMs to operate at higher temperatures if thermal control is not implemented. The insulation materials may deteriorate because of these high temperatures, which would lower the motor's dependability and efficiency. The motor's efficiency usually drops as the temperature rises. This is because greater temperatures cause the core and wind to become more

electrically resistant, which raises losses. Because the heat may not be adequately expelled from the system, the motor also loses efficiency in heat dissipation.

The usefulness of heat management techniques for permanent magnet synchronous motors (PMSMs) is revealed by experimental findings and real-world applications. Engineers have discovered several important conclusions about how temperature management affects motor performance, efficiency, and dependability through practical testing and application. These observations are derived from a variety of industry and scientific contexts, including wind turbines, industrial automation, electric vehicles (EVs), and aerospace [41]. Effective thermal control has been demonstrated to greatly increase the overall efficiency of PMSMs in practical applications, such as electric vehicles (EVs). For example, EV motors with liquid cooling systems in experimental setups showed a discernible drop in motor temperature, which resulted in lower winding resistance and fewer electrical losses. Better energy efficiency resulted from this, enabling the motor to sustain high torque and power output without experiencing undue heat accumulation.

VIII. FUTURE TRENDS IN THERMAL MANAGEMENT

The integration of artificial intelligence (AI) into the thermal management of permanent magnet synchronous motors (PMSMs) represents a cutting-edge approach to optimizing motor performance and efficiency. By harnessing AI's capabilities in data analysis, pattern recognition, and real-time decision-making, predictive thermal control systems can significantly enhance the performance and reliability of PMSMs, particularly in demanding applications such as electric vehicles (EVs), aerospace, and industrial machinery. Temperature data gathered from several sensors integrated inside the motor, such as the stator, rotor, and bearings, can be analyzed by AI algorithms. These algorithms forecast the motor's temperature at any given time by utilizing historical data, real-time temperature readings, and environmental variables (such as load, speed, and ambient temperature). Neural networks and regression algorithms are examples of machine learning models that can recognize trends in temperature variations and predict future heat production.

The development of novel cooling fluids and materials is crucial for enhancing the thermal performance of permanent magnet synchronous motors (PMSMs), particularly in high-power-density and high-efficiency applications [22]. These advanced cooling solutions aim to provide superior heat transfer capabilities, reduce motor operating temperatures, and improve overall system reliability. In the pursuit of more efficient thermal management, several novel cooling fluids and materials have emerged, each offering unique properties that can significantly enhance PMSM thermal control.

A viable approach to PMSM thermal management is the use of innovative cooling fluids and materials, especially for high-performance applications that require long-term dependability and effective heat dissipation. Advanced carbon-based fluids, PCMs, dielectric fluids, and Nano fluids are already shown a great deal of promise for enhancing thermal performance. These materials promote the ongoing development of PMSM technology in sectors including electric vehicles, aircraft, and renewable energy, make it

possible for more compact and effective cooling solutions, and improve motor dependability. These technologies will probably be essential in addressing the thermal management issues of the upcoming generation of high-performance motors as they develop [42].

The design and production of permanent magnet synchronous motors (PMSMs) are being completely transformed by additive manufacturing (AM), also referred to as 3D printing, which makes it possible to create intricate geometries and structures that were previously hard or impossible to accomplish with conventional manufacturing methods. Because it makes it possible to include cutting-edge cooling features straight into the motor components, this technology is especially useful for thermal optimization since it enhances heat dissipation and thermal management in general. Customized internal cooling channels can be designed and created in the stator, rotor, and other motor components thanks to additive manufacturing. By increasing the area of contact between the cooling fluid and motor surfaces, these complex channels can be made to flow more efficiently and improve heat transmission. Complex cooling channels are frequently difficult to integrate using conventional manufacturing techniques, but AM can quickly create designs that maximize the thermal route, resulting in cooling systems that are more efficient.

Co-simulation is a sophisticated method that models and analyzes complex systems by combining several simulation tools, enabling more thorough and precise predictions of a system's behavior. Co-simulation optimizes motor design, performance, and thermal management in the context of permanent magnet synchronous motors (PMSMs) by combining electrical, mechanical, and thermal models. Engineers may create more effective cooling plans and raise the overall dependability and efficiency of motors by simulating electrical and thermal interactions at the same time.

Researchers and engineers are looking into alternate solutions, such as better heat sink designs, hybrid cooling strategies, and enhanced thermal interface materials, to address these issues. Finding the best solutions requires quantitative comparisons, such as cost-benefit evaluations of various cooling techniques. The trade-offs between efficiency, cost, and scalability can be further demonstrated by real-world case studies from sectors like aircraft and electric vehicles, which can offer insightful information for future developments. The need for more efficient thermal solutions has prompted the development of hybrid thermal management systems, which handle the complex and varied thermal loads encountered in PMSMs as they continue to be used in high-performance applications like industrial machinery, electric vehicles (EVs), and aerospace. The combination of liquid and air cooling is one of the most popular hybrid thermal management systems. Even though air cooling is inexpensive, lightweight, and rather easy, it might not be enough for high-power-density PMSMs since it can be difficult to effectively remove huge amounts of heat. However, liquid cooling is more efficient in removing heat, but it necessitates more intricate infrastructure and equipment.

The intricacy and high expense of efficient cooling methods make managing heat in sophisticated systems

extremely difficult. Although they need costly materials, specialized designs, and complex production processes, methods like liquid cooling, phase change materials (PCM), and heat pipes provide greater temperature management. Therefore, a significant obstacle to their wider adoption is the cost of creation and implementation.

IX. CHALLENGES AND LIMITATIONS

High-performance PMSM adoption of improved thermal management systems are hampered by a few important factors. Since sophisticated cooling systems like liquid cooling, phase change materials (PCM), and heat pipes necessitate large material investments, unique designs, and prototypes, one of the main obstacles is the high development and implementation costs. Particularly in space-constrained applications like electric vehicles and airplanes, these solutions frequently need intricate integration with motor topologies, which raises the design difficulties and makes striking a balance between compactness and cooling efficiency more difficult. The interplay of thermal and electrical behavior also presents difficulties since sophisticated cooling techniques may inadvertently alter electromagnetic characteristics, resulting in problems like uneven temperature gradients or magnet demagnetization. The adoption of advanced thermal systems is further slowed by a lack of experience in their design and modelling, since these methods frequently call for specialized knowledge and sophisticated simulation tools that are not always available. The complexity is increased by environmental and safety issues, such as the danger of leaks and fires or the toxicity and disposal of specific coolants. Additionally, there are trade-offs in energy efficiency because active cooling systems use more energy, which could offset the efficiency gains from better thermal management.

Several obstacles prevent high-performance PMSMs from adopting sophisticated heat management approaches. Since methods like liquid cooling, phase change materials (PCM), and heat pipes call for costly materials, specialized designs, and intricate manufacturing processes, high development and implementation costs represent a major obstacle. Furthermore, integration is challenging due to design complexity, especially in fields like aerospace and electric cars where weight reduction and compactness are crucial. Since many sophisticated cooling technologies are highly customized and difficult to adapt to large-scale manufacturing, scalability for mass production is still a challenge. Because correct co-simulation of electrical and thermal behaviors requires specialized knowledge that is not always readily available, the absence of experience and sophisticated modelling tools creates an additional degree of difficulties. The use of these methods is made more difficult by environmental and safety concerns, such as the possible toxicity of some coolants, disposal problems, and the possibility of leaks or fire hazards. Additionally, there are trade-offs in energy efficiency because active cooling techniques use more power, which might cancel out the efficiency gains from better thermal performance.

Adoption of sophisticated heat management approaches for high-performance PMSMs is significantly hampered by reliability and long-term performance concerns. To guarantee steady performance over time, several cooling techniques,

including liquid cooling, phase change materials (PCM), and heat pipes, need to undergo rigorous durability testing. Long-term exposure to high temperatures, thermal cycling, and mechanical stressors can cause wear, cracks, or leaks in cooling channels, decreasing their efficacy and raising maintenance needs. This makes material degradation a serious concern. Coolant deterioration, corrosion, and leakage are major problems in liquid cooling systems that can cause decreased efficiency or system failure. Phase separation and material ageing also affect PCM-based cooling, which over time may have an impact on heat absorption and thermal conductivity.

The scalability of emerging thermal management technologies for high-performance PMSMs remains a critical challenge, particularly when transitioning from prototype designs to mass production. Many advanced cooling techniques, such as liquid cooling, phase change materials (PCM), heat pipes, and nanofluids, are highly customized to specific applications, making them difficult to standardize for large-scale manufacturing. The complexity of integration into compact and lightweight motor designs often requires precise engineering and specialized manufacturing processes, which may not align with the existing production infrastructure. For example, liquid-cooled systems require carefully designed channels and seals to prevent leaks, which increases manufacturing costs and assembly time.

To ensure that emergent technologies can be scaled effectively without sacrificing performance or reliability, it is necessary to invest in process optimization, material standardization, and creative design techniques to overcome these obstacles. To advance thermal management solutions in high-performance PMSMs, it will be crucial to close the gap between state-of-the-art research and extensive industry application.

X. CONCLUSIONS AND RECOMMENDATIONS

High-performance PMSMs' efficiency, dependability, and operational lifespan have been greatly increased by recent developments in thermal management approaches, especially in demanding applications like renewable energy systems, electric vehicles, and aircraft. High thermal loads in compact motor designs have been addressed by innovations including liquid cooling, phase change materials (PCM), heat pipes, and nanofluids, which have made heat dissipation more efficient. By improving the quality of thermal simulations, advanced modelling techniques such as lumped parameter thermal networks (LPTN) and finite element analysis (FEA) have made it easier to integrate cooling systems. The creation of standardized testing procedures, economical production methods, and environmentally friendly cooling options should be the main goals of future initiatives to remove these obstacles. These developments demonstrate how important a role thermal management technology could play in improving PMSM longevity and performance in high-performance applications. The main conclusions of recent developments in thermal management for high-performance PMSMs emphasize how crucial effective heat dissipation techniques are becoming to improve motor longevity, performance, and dependability. Phase change materials (PCM), heat pipes, liquid cooling, and nanofluids have all been successfully used to lower

thermal stress and increase efficiency, especially in high-power-density applications like aerospace and electric cars. Cost-effective, flexible, and extremely effective thermal management systems should be given top priority in future PMSM designs, which should balance durability and manufacturability with performance gains. To advance next-generation PMSM technology for demanding applications, it will be imperative to address these important difficulties. Scalability is still a major challenge in addition to cost. Although these cooling techniques work well in controlled settings, incorporating them into large-scale applications—like aerospace systems or electric vehicles (EVs) requires significant design changes and stringent testing. Furthermore, factors that affect long-term performance and operating efficiency, such as material degradation, leakage hazards, and maintenance complexity, can lead to dependability difficulties.

Future studies on thermal management for high-performance PMSMs should concentrate on creating scalable, reasonably priced, and extremely effective cooling systems that work well with the designs of next-generation motors. Optimizing liquid cooling systems, which include better channel designs and the use of cutting-edge, environmentally friendly coolants to maximize heat dissipation and reduce leakage hazards, is one crucial area. To solve long-term reliability challenges such material deterioration, phase separation, and stability under different operating circumstances, more research into phase change materials (PCM) and nanofluids is required.

REFERENCES

- [1] A. Sergakis, M. Salinas, N. Gkiolekas, and K. N. Gyftakis, "A Review of Condition Monitoring of Permanent Magnet Synchronous Machines: Techniques, Challenges and Future Directions," *Energies*, vol. 18, no. 5, p. 1177, 2025, <https://doi.org/10.3390/en18051177>.
- [2] M. H. Ali, A. A. R. Ramadan, D. M. Abass, and M. H. Ali, "Analysis and simulation model of three phase Permanent Magnet Synchronous Motor Drive (PMSM)," in *E3S Web of Conferences*, EDP Sciences, p. 1011, 2024, <https://doi.org/10.1051/e3sconf/202454201011>.
- [3] F. Wang, Z. Zhang, X. Mei, J. Rodríguez, and R. Kennel, "Advanced control strategies of induction machine: Field oriented control, direct torque control and model predictive control," *Energies*, vol. 11, no. 1, p. 120, 2018, <https://doi.org/10.3390/en11010120>.
- [4] A. Loutfy and T. Elhag, "A Review of Determining Suitable Maintenance Strategy," in *CIB Conferences*, p. 129, 2025, <https://doi.org/10.7771/3067-4883.1961>.
- [5] T. Orłowska-Kowalska *et al.*, "Fault Diagnosis and Fault-Tolerant Control of PMSM Drives-State of the Art and Future Challenges," *IEEE Access*, vol. 10, pp. 59979–60024, 2022, <https://doi.org/10.1109/ACCESS.2022.3180153>.
- [6] O. Wallscheid, "Thermal Monitoring of Electric Motors: State-of-the-Art Review and Future Challenges," *IEEE Open Journal of Industry Applications*, vol. 2, pp. 204–223, 2021, <https://doi.org/10.1109/OJIA.2021.3091870>.
- [7] B. Venkataraman, B. Godsey, W. Premerlani, E. Shulman, M. Thakur, and R. Midence, "Fundamentals of a motor thermal model and its applications in motor protection," in *2005 58th Annual Conference for Protective Relay Engineers*, 2005, pp. 127–144, <https://doi.org/10.1109/CPRE.2005.1430428>.
- [8] L. Evangelisti, C. Guattari, P. Gori, and F. Bianchi, "Heat transfer study of external convective and radiative coefficients for building applications," *Energy and Buildings*, vol. 151, pp. 429–438, 2017, <https://doi.org/10.1016/j.enbuild.2017.07.004>.
- [9] A. Zeaiter, "Thermal Modeling and Cooling of Electric Motors: Application to the Propulsion of Hybrid Aircraft," ISAE-ENSMA Ecole Nationale Supérieure de Mécanique et d'Aérotechnique-Poitiers, 2021, <https://theses.hal.science/tel-03158868>.

- [10] Z. Huang, J. Fang, X. Liu, and B. Han, "Loss Calculation and Thermal Analysis of Rotors Supported by Active Magnetic Bearings for High-Speed Permanent-Magnet Electrical Machines," *IEEE Transactions on Industrial Electronics*, vol. 63, no. 4, pp. 2027–2035, 2016, <https://doi.org/10.1109/TIE.2015.2500188>.
- [11] R. R. Talla, "Robotic Automation in Thermal Management: Optimizing Heat Transfer for High-Performance Systems," *Journal of Fareast International University*, vol. 2024, no. 1, pp. 1–11, 2024, <https://hal.science/hal-04895422v1>.
- [12] O. Wallscheid and J. Böcker, "Global identification of a low-order lumped-parameter thermal network for permanent magnet synchronous motors," *IEEE Transactions on Energy Conversion*, vol. 31, no. 1, pp. 354–365, 2016, <https://doi.org/10.1109/TEC.2015.2473673>.
- [13] H. F. Zhou, Y. Q. Ni, and J. M. Ko, "Constructing input to neural networks for modeling temperature-caused modal variability: Mean temperatures, effective temperatures, and principal components of temperatures," *Engineering Structures*, vol. 32, no. 6, pp. 1747–1759, 2010, <https://doi.org/10.1016/j.engstruct.2010.02.026>.
- [14] J. Chukwunweike and H. D. Salaudeen, "Advanced Computational Methods for Optimizing Mechanical Systems in Modern Engineering Management Practices," *International Journal of Research Publication and Reviews*, vol. 6, no. 3, pp. 8533–8548, 2025, <https://doi.org/10.55248/gengpi.6.0325.12178>.
- [15] S. V. Garimella *et al.*, "Thermal challenges in next-generation electronic systems," *IEEE Transactions on Components and Packaging Technologies*, vol. 31, no. 4, pp. 801–815, 2008, <https://doi.org/10.1109/TCAPT.2008.2001197>.
- [16] L. Di Leonardo, F. Parasiliti, M. Tursini, and M. Villani, "Transient analysis of PM synchronous motor drives by finite element model co-simulation," in *IECON Proceedings (Industrial Electronics Conference)*, 2013, pp. 6834–6840, <https://doi.org/10.1109/IECON.2013.6700264>.
- [17] D. Huerlimann, "Model Based Optimization of Internal Heat Sources in Machine Tools," ETH Zurich, 2002, <https://doi.org/10.3929/ethz-b-000206812>.
- [18] F. Awungabeh, "Doctoral thesis investigation of a novel airflow cooling system for high power-density permanent magnet machine," 2024, https://ynu.repo.nii.ac.jp/record/2001054/files/awungabeh_flavis_akawu-ng-thesis.pdf.
- [19] S. Xu, H. Zhang, and Z. Wang, "Thermal Management and Energy Consumption in Air, Liquid, and Free Cooling Systems for Data Centers: A Review," *Energies*, vol. 16, no. 3, p. 1279, 2023, <https://doi.org/10.3390/en16031279>.
- [20] E. Gundabattini, A. Mystkowski, R. Raja Singh, and S. D. Gnanaraj, "Water cooling, PSG, PCM, Cryogenic cooling strategies and thermal analysis (experimental and analytical) of a Permanent Magnet Synchronous Motor: a review," *Sadhana - Academy Proceedings in Engineering Sciences*, vol. 46, no. 3, p. 124, 2021, <https://doi.org/10.1007/s12046-021-01650-z>.
- [21] K. J. Chua, S. K. Chou, W. M. Yang, and J. Yan, "Achieving better energy-efficient air conditioning - A review of technologies and strategies," *Applied Energy*, vol. 104, pp. 87–104, 2013, <https://doi.org/10.1016/j.apenergy.2012.10.037>.
- [22] A. G. Shewalkar, A. S. Dhoble, and V. P. Thawkar, "Review on cooling techniques and analysis methods of an electric vehicle motor," *Journal of Thermal Analysis and Calorimetry*, vol. 149, no. 12, pp. 5919–5947, 2024, <https://doi.org/10.1007/s10973-024-13091-x>.
- [23] S. Khalid, "Advanced electric propulsion systems for hybrid electric vehicles: Design, control, and performance optimization," in *Hybrid Electric Vehicles and Distributed Renewable Energy Conversion: Control and Vibration Analysis*, IGI Global Scientific Publishing, pp. 1–54, 2024, <https://doi.org/10.4018/979-8-3693-5797-2.ch001>.
- [24] M. Monadi, M. Nabipour, F. Akbari-Behbahani, and E. Pouresmaeil, "Speed Control Techniques for Permanent Magnet Synchronous Motors in Electric Vehicle Applications Toward Sustainable Energy Mobility: A Review," *IEEE Access*, vol. 12, pp. 119615–119632, 2024, <https://doi.org/10.1109/ACCESS.2024.3450199>.
- [25] H. Liu and B. X. Du, "Effects of Magnetic Field on Dielectric and Insulation Properties: A Review," *IEEE Transactions on Dielectrics and Electrical Insulation*, vol. 32, no. 5, pp. 2497–2512, 2025, <https://doi.org/10.1109/TDEI.2025.3573307>.
- [26] E. Gundabattini, A. Mystkowski, A. Idzkowski, R. Raja Singh, and D. G. Solomon, "Thermal mapping of a high-speed electric motor used for traction applications and analysis of various cooling methods-a review," *Energies*, vol. 14, no. 5, p. 1472, 2021, <https://doi.org/10.3390/en14051472>.
- [27] C. Dong, Y. Qian, Y. Zhang, and W. Zhuge, "A Review of Thermal Designs for Improving Power Density in Electrical Machines," *IEEE Transactions on Transportation Electrification*, vol. 6, no. 4, pp. 1386–1400, 2020, <https://doi.org/10.1109/TTE.2020.3003194>.
- [28] Y. G. Lv, G. P. Zhang, Q. W. Wang, and W. X. Chu, "Thermal Management Technologies Used for High Heat Flux Automobiles and Aircraft: A Review," *Energies*, vol. 15, no. 21, p. 8316, 2022, <https://doi.org/10.3390/en15218316>.
- [29] A. Deriszadeh and F. de Monte, "On heat transfer performance of cooling systems using nanofluid for electric motor applications," *Entropy*, vol. 22, no. 1, p. 99, 2020, <https://doi.org/10.3390/e22010099>.
- [30] S. M. Sohel Murshed and C. A. Nieto de Castro, "A critical review of traditional and emerging techniques and fluids for electronics cooling," *Renewable and Sustainable Energy Reviews*, vol. 78, pp. 821–833, 2017, <https://doi.org/10.1016/j.rser.2017.04.112>.
- [31] B. Anwajler, "Potential of 3D Printing for Heat Exchanger Heat Transfer Optimization—Sustainability Perspective," *Inventions*, vol. 9, no. 3, p. 60, 2024, <https://doi.org/10.3390/inventions9030060>.
- [32] J. Prosper, "Smart Thermal Monitoring Systems IoT-Enabled Temperature Sensing for Rotating Equipment (1)," 2025, <https://www.researchgate.net/publication/390233231>.
- [33] M. Jiménez-Arreola, R. Pili, F. Dal Magro, C. Wieland, S. Rajoo, and A. Romagnoli, "Thermal power fluctuations in waste heat to power systems: An overview on the challenges and current solutions," *Applied Thermal Engineering*, vol. 134, pp. 576–584, 2018, <https://doi.org/10.1016/j.applthermaleng.2018.02.033>.
- [34] M. A. Vadivelu, C. R. Kumar, and G. M. Joshi, "Polymer composites for thermal management: a review," *Composite Interfaces*, vol. 23, no. 9, pp. 847–872, 2016, <https://doi.org/10.1080/09276440.2016.1176853>.
- [35] M. A. Fentahun and M. A. Savas, "Materials Used in Automotive Material and Material Selection Using Ashby Charts," *International Journal of Materials Engineering*, vol. 8, no. 3, pp. 40–54, 2018, <https://doi.org/10.5923/j.ijme.20180803.02>.
- [36] S. Simões, "High-Performance Advanced Composites in Multifunctional Material Design: State of the Art, Challenges, and Future Directions," *Materials*, vol. 17, no. 23, p. 5997, 2024, <https://doi.org/10.3390/ma17235997>.
- [37] N. Mumtaz *et al.*, "Fillers and methods to improve the effective (out-plane) thermal conductivity of polymeric thermal interface materials – A review," *Heliyon*, vol. 10, no. 3, 2024, <https://doi.org/10.1016/j.heliyon.2024.e25381>.
- [38] C. Liao, N. Bianchi, and Z. Zhang, "Recent Developments and Trends in High-Performance PMSM for Aeronautical Applications," *Energies*, vol. 17, no. 23, p. 6199, 2024, <https://doi.org/10.3390/en17236199>.
- [39] R. K. Shah, B. Thonon, and D. M. Benforado, "Opportunities for heat exchanger applications in environmental systems," *Applied Thermal Engineering*, vol. 20, no. 7, pp. 631–650, 2000, [https://doi.org/10.1016/S1359-4311\(99\)00045-9](https://doi.org/10.1016/S1359-4311(99)00045-9).
- [40] A. Faghri, "Heat pipes: Review, opportunities and challenges," *Frontiers in Heat Pipes*, vol. 5, no. 1, Apr. 2014, <https://doi.org/10.5098/fhp.5.1>.
- [41] A. R. Nejad *et al.*, "Wind turbine drivetrains: State-of-the-art technologies and future development trends," *Wind Energy Science*, vol. 7, no. 1, pp. 387–411, 2022, <https://doi.org/10.5194/wes-7-387-2022>.
- [42] E. Laloya, Ó. Lucía, H. Samago, and J. M. Burdío, "Heat Management in Power Converters: From State of the Art to Future Ultrahigh Efficiency Systems," *IEEE Transactions on Power Electronics*, vol. 31, no. 11, pp. 7896–7908, 2016, <https://doi.org/10.1109/TPEL.2015.2513433>.