

Challenges and Advances in Electrical and Thermal Modeling of High-Precision PMSM Drives

Md Ali Azom^{1,*}, Md. Yakub Ali Khan²

¹ Department of Mechanical and Power Engineering, Nanjing Tech University, China

² Department of Electrical and Electronic Engineering, World University of Bangladesh, Uttara, Dhaka Bangladesh

Email: ¹ aliajom786@gmail.com, ² yakub.bimt@gmail.com

*Corresponding Author

Abstract—This review examines the challenges and advancements in electrical and thermal modeling of PMSM systems, emphasizing their interdependence and practical applications. Permanent Magnet Synchronous Motors (PMSMs) are essential for high-precision applications including electric vehicles, robots, and aerospace systems because of their exact controllability, high efficiency, and high-power density. However, maximizing PMSM drive performance necessitates a thorough comprehension of both their thermal and electrical properties. The difficulties and developments in electrical and thermal modeling for PMSMs are thoroughly examined in this paper, with a focus on high-precision applications. The research starts by going over the basics of PMSM drives and their operating parameters. Next, it examines important electrical modeling methods, such as finite element methods, dq-axis transformations, and approaches to nonlinearities like saturation and harmonics. The conversation goes on to explore thermal modeling techniques, emphasizing computational fluid dynamics, lumped parameter models, and finite element thermal analysis. The review emphasizes how important integrated electrical-thermal models are for accurately predicting the coupled dynamics of electrical performance and heat generation in high-performance applications. Innovative solutions including machine learning-driven models, hybrid approaches, and the usage of digital twins are considered alongside major problems like computational complexity, parameter identification, and real-time implementation. In addition, this paper looks at real-world case studies that demonstrate how sophisticated modeling approaches can improve PMSM designs and guarantee thermal stability in a range of operating scenarios. The development of real-time simulation techniques, investigation of new cooling materials, and improvements in multi-physics modeling are among the final research directions mentioned. Future directions include advancements in real-time simulation, novel cooling materials, and multi-physics modeling. By highlighting this early integration, the study offers a cohesive framework that improves comprehension of coupled electro-thermal phenomena, setting it apart from traditional research and making it an invaluable tool for engineers and researchers.

Keywords—PMSM Drives, Electrical Modeling, Thermal Modeling; Coupled Models, High-Precision Applications, Machine Learning

I. INTRODUCTION

Because of their remarkable efficiency, accuracy, and dependability, permanent magnet synchronous motors, or PMSMs, are essential in contemporary applications. By using permanent magnets, these motors reduce energy losses and provide better performance in energy-sensitive applications like renewable energy systems and electric cars. They are

perfect for weight-sensitive and space-constrained applications like robotics and aircraft because of their small size and excellent torque-to-weight ratio [1]. For high-precision applications in industrial automation, CNC machines, and medical equipment, PMSMs provide exact control over torque and speed. They are ideal for electric propulsion in hybrid and electric vehicles since they function effectively under a variety of loads and speeds. Furthermore, the lack of brushes and sliding rings increases their dependability and lowers maintenance needs, guaranteeing durability in challenging industrial settings [2]. With uses in solar power systems, wind turbines, and military technology, PMSMs provide a substantial contribution to both technological advancement and sustainability. Additionally, they are positioned as a cornerstone of Industry 4.0, fostering innovation across a variety of industries, thanks to their integration with IoT, AI, and advanced control systems [3].

Because of the intricate and interconnected structure of motor behavior, electrical and thermal modeling of Permanent Magnet Synchronous Motor (PMSM) drives present several difficulties. Electrically, it is crucial but challenging to accurately depict flux leakage, saturation effects, and nonlinearities in the magnetic circuits, particularly under changing operating conditions [4]. The part of a magnetic field that veers off course within a magnetic circuit, as in transformers, inductors, electric motors, is known as flux leakage. A portion of the magnetic flux escapes into the surrounding air or other materials rather than being completely contained within the core material, which results in energy loss, decreased efficiency, and possible electromagnetic interference. Flux leakage is the term used to describe the portion of a magnetic field that deviates from its intended path within a magnetic circuit, such as in transformers, inductors, or electric motors. Instead of being entirely contained within the core material, some of the magnetic flux escapes into the surrounding air or other materials, causing energy loss, reduced efficiency, and potential electromagnetic interference. The interdependent relationship between a system's electrical and thermal characteristics is referred to as coupled electrical-thermal dynamics. Heat produced by electrical components during operation has an impact on their resistance, performance, and overall efficiency. On the other hand, electrical characteristics like conductivity and carrier mobility are impacted by temperature variations. This relationship is particularly critical in high-power electronics, semiconductors, and energy systems, where precise thermal

management is crucial to preserve stability and prevent failure.

Temperature and load dependencies make estimating real-time parameters like resistance and inductance even more challenging. Accurately modeling heat transmission and dissipation methods, such as conduction, convection, and radiation, is still difficult, even though thermal understanding of heat generation from losses in the stator, rotor, and magnets is crucial. Because thermal behavior is influenced by electrical performance and vice versa, coupled electrical and thermal interactions introduce an additional level of complexity [5]. It investigates how electrical and thermal processes are interdependent, assesses state-of-the-art modeling and simulation techniques, and looks at how they are used in high-performance real-world systems [6]. With a focus on applications in robotics, electric vehicles, aircraft, and renewable energy systems, the review also emphasizes the incorporation of cutting-edge technology like artificial intelligence and digital twins to improve the precision and effectiveness of PMSM models. Draw attention to the nonlinearities, parameter fluctuations, and real-time adaptability that are among the practical and technological difficulties in simulating the electrical and thermal behaviors of PMSM drives. Examine cutting-edge modeling approaches for coupled electrical-thermal dynamics with an emphasis on scalability, accuracy, and computing efficiency. Examine how cutting-edge technologies like digital twin frameworks, hybrid models, and machine learning might transform PMSM modeling and control techniques. Show how advanced modeling approaches are applicable to vital applications such as high-precision manufacturing processes, renewable energy systems, and electric automobiles [7].

II. FUNDAMENTALS OF PMSM DRIVES

Because of their great efficiency, dependability, and small size, permanent magnet synchronous motors, or PMSMs, are used extensively in contemporary applications. A three-phase PMSM is a sophisticated motor that creates a smooth and effective rotating magnetic field by using three-phase windings on the stator and permanent magnets on the rotor [8]. Torque is produced by the interaction of this rotating field with the magnetic field of the rotor. Permanent magnets composed of high-performance materials such as samarium-cobalt or neodymium are found in the rotor. Efficiency is increased since these magnets produce a steady magnetic field without the need for external power. Three-phase windings are installed in slots around the stator's perimeter [9]. These windings produce a revolving magnetic field when they are powered. The frequency and amplitude of the magnetic field are accurately controlled by an external three-phase inverter that provides sinusoidal, or pulse-width modulated (PWM) currents to the stator windings. To keep the rotor and stator fields in sync, a control system, frequently using Field-Oriented Control (FOC), modifies the inverter's output.

A balanced three-phase current flowing through the stator windings creates a revolving magnetic field. This field moves at a synchronous speed that is dependent on the motor's pole count and current frequency. With the help of its permanent magnets, the rotor aligns itself with the rotating magnetic field to generate torque. Unlike induction motors, PMSMs

operate without slip, meaning that the rotor speed exactly matches the stator field speed. A constant torque is produced by the interaction of the stator's revolving field and the rotor's magnetic field [10]. The strength of the rotor magnets and the current flowing through the stator windings determine how much torque is produced. Even at low speeds, smooth operation is guaranteed by the three-phase configuration's steady torque production and low ripples. By using permanent magnets, the rotor losses that come with conventional induction motors are eliminated, increasing overall efficiency. From little home items to massive industrial gear, PMSMs can be made for a variety of uses. Because of their high-power density and accurate speed control, three-phase PMSMs are recommended for EVs. utilized in CNC machines, robots, and conveyors where precision and effectiveness are essential. incorporated into solar tracking systems and wind turbines to provide sustainable energy [11]. Three-phase PMSMs combine a strong architecture with cutting-edge control methods to provide unparalleled performance and adaptability in a wide range of applications. Fig. 1 shows the Parameter Estimation of Permanent Magnet Synchronous Motor




Fig. 1. Parameter estimation of permanent magnet synchronous motor

The performance of three-phase Permanent Magnet Synchronous Motors (PMSMs) is significantly influenced by electrical, thermal, and mechanical elements, all of which are necessary to ensure efficiency, reliability, and lifetime. Electrical properties such as back electromotive force (EMF), winding resistance, inductance, and current density have a direct effect on the motor's energy conversion efficiency, torque output, and dynamic responsiveness [12]. For improved electrical performance, power factor optimization and I²R loss reduction are essential. For stability and to avoid performance degradation from overheating, thermal characteristics such as heat dissipation, thermal resistance, and magnet temperature are essential [13]. To improve thermal management, efficient cooling techniques like liquid cooling systems or forced air cooling are frequently used. The motor's dynamic behavior, smooth operation, and lifespan are influenced by mechanical factors such rotor inertia, bearing quality, structural integrity, and vibration levels. A comprehensive approach to optimization is necessary due to the interaction of several parameters, such as the influence of electrical losses on heat generation or thermal expansion on mechanical alignment. PMSMs can achieve improved performance in a variety of applications, ranging from industrial automation to electric vehicles, by resolving these interdependencies and utilizing cutting-edge materials, control tactics, and cooling approaches [14].

One important element affecting the performance, efficiency, and dependability of Permanent Magnet Synchronous Motors (PMSMs) is the interaction between electrical and thermal dynamics. The main causes of heat generation in the motor are electrical losses, such as I^2R losses in the windings and core losses in the stator [15]. The temperature rise results from these losses impacts several parts, including bearings, winding insulation, and permanent magnets. High temperatures have the potential to weaken magnets, especially if they get close to the Curie point. This can reduce torque production and motor efficiency [16]. Furthermore, too much heat can deteriorate winding insulation, raising the risk of short circuits and electrical losses even more. Electrical qualities are also affected by thermal dynamics; for example, greater temperatures make conductive materials more resistive, which increases I^2R losses and makes the thermal load worse. To reduce heat buildup, this cyclical relationship emphasizes the significance of efficient thermal management systems, such as sophisticated cooling mechanisms and thermally conductive materials. Optimizing PMSM performance, guaranteeing dependability under heavy loads, and prolonging the motor's operational lifespan in challenging applications all depend on addressing the interdependence of electrical and thermal dynamics [17].

III. PMSM DRIVE ELECTRICAL MODELLING

In electrical and electronic systems analysis, analytical models like dq-axis transformations and equivalent circuit models are crucial instruments. By depicting complicated systems as networks of idealized parts, such as resistors, capacitors, and inductors, equivalent circuit models make it simpler to analyze how they behave under different circumstances [18]. These models are widely used in fields such as electronics design, power systems, and electrochemical impedance spectroscopy. Finite element analysis (FEA) for electrical performance prediction [19]. Conversely, dq-axis transformations facilitate the control and analysis of AC machines and power systems by converting three-phase AC variables into a two-axis reference frame (direct and quadrature axes). This technique, which decouples torque and flux control for increased efficiency and dynamic performance, is frequently used in electrical drives, renewable energy systems, and power system stability studies. It incorporates mathematical transformations such as the Clarke and Park transformations. Both strategies are essential for developing contemporary energy and electrical systems [20].

Saturation, harmonics, and eddy currents are examples of nonlinearities in electrical modelling that have a big influence on electrical system analysis and performance. When a rise in magnetic field intensity no longer causes proportionate increases in magnetic flux density, magnetic materials reach saturation and exhibit nonlinear behavior [21]. This is crucial because saturation impacts performance and efficiency in electric machines, transformers, and inductors. Conversely, harmonics are caused by non-sinusoidal waveforms or switching devices, which introduce higher frequency components that distort the waveforms of voltage and current, resulting in electromagnetic interference and power losses. Time-varying magnetic fields can create circulating

currents called eddy currents in conductive materials, which can lead to energy loss like heat and decreased system efficiency. To increase the precision, efficiency, and dependability of contemporary electrical and electronic systems, accurate modelling and mitigation of these nonlinearities are crucial [22].

Advances in electrical modeling techniques have revolutionized the design, analysis, and optimization of modern electrical systems. These approaches address difficult electrical modeling problems by utilizing developments in computer techniques, materials science, and artificial intelligence. A crucial tool for precisely resolving electromagnetic field problems, finite element analysis (FEA) enables in-depth analysis of parts like motors and transformers. AI and machine learning-driven data-driven models are used for predictive maintenance, problem identification, and real-time system improvement. Moreover, multi-physics simulation tools now incorporate mechanical, thermal, and electrical phenomena, providing comprehensive understanding of system behavior [23]. High-fidelity time-domain solvers enable the in-depth investigation of transient events, while improvements in circuit-level modelling have improved the correctness of comparable circuit representations. These developments assist the expanding needs of sectors like smart grids, electric vehicles, and renewable energy by ensuring increased electrical system efficiency, dependability, and adaptability.

IV. THERMAL MODELING OF PMSM DRIVES

Copper losses, core losses, and stray losses are some of the sources of heat generation in electrical systems, and they all lead to inefficiencies and difficulties with thermal management. Significant energy dissipation, especially in transformers and motor windings, results from copper losses caused by resistance in conductors, where electrical current generates heat proportional to the square of the current [24]. The magnetization and demagnetization of the core material, as well as induced currents in the core when exposed to alternating magnetic fields, cause core losses, which include hysteresis and eddy current losses. Frequency, flux density, and material characteristics all affect these losses. Less predictable stray losses are caused by leakage flux and harmonics that create eddy currents in non-target locations like windings and structural components. Designing efficient cooling mechanisms for electrical devices and systems, increasing system reliability, and improving system efficiency all depend on accurate modelling and mitigation of these heat sources [25].

A Permanent Magnet Synchronous Motor's (PMSM) longevity and performance are greatly influenced by its thermal behavior. The efficiency and dependability of motors can be severely impacted by excessive heat produced during operation, which is mostly caused by copper losses, core losses, and stray losses. High temperatures weaken permanent magnets' magnetic characteristics, which lowers their strength and lowers torque output and overall efficiency. Hot spots brought on by an uneven heat distribution can worsen material deterioration and perhaps result in mechanical deformation [26]. To lessen these problems, efficient thermal management via enhanced cooling systems, optimized design, and sophisticated thermal modelling is

crucial. PMSMs can achieve improved performance, increased economy, and longer operational life by preserving thermal stability, which makes them more appropriate for demanding applications in sectors like renewable energy and the automobile industry [27].

For electrical device heat generation and dissipation to be predicted and controlled, thermal modelling techniques are essential. Lumped Parameter Models (LPM), Finite Element Thermal Analysis (FETA), and Computational Fluid Dynamics (CFD) are some of the best techniques. Lumped Parameter Models (LPM) Simplifies the thermal behavior of a system by representing it as a network of discrete thermal resistances and capacitances. Commonly used in quick thermal simulations of motors, transformers, and power electronics, where the goal is to approximate temperature distribution without extensive computational resources. Fast, low computational cost, and suitable for early design stages or real-time applications. Thermal analysis using finite elements (FETA) provides a thorough temperature profile by solving the heat conduction equations across the geometry of a system using finite element methods. Perfect for in-depth thermal analyses of motor and transformer windings, cores, and heat sinks. high precision and the capacity to simulate intricate material characteristics and geometries. requires a large amount of setup time and processing power [28]. In thermal management, computational fluid dynamics (CFD) models heat transfer and fluid flow to examine convective cooling and ventilation in electrical systems. frequently utilized in the design of cooling systems for high-performance electric motors, electric cars, and power electronics. allows for the optimization of cooling solutions by capturing the interplay between fluid dynamics and thermal behavior.

The precision and effectiveness of heat management in electrical and electronic systems have been greatly improved by recent developments in thermal modelling techniques. Predictive thermal modelling has been made possible by the combination of machine learning and AI-driven algorithms, enabling real-time evaluation and dynamic cooling strategy optimization [29]. Thermal, electrical, and mechanical studies are now combined in multi-physics models to offer a thorough understanding of system interactions and their thermal impacts. Complex geometries, transient thermal behaviors, and non-linear material properties can now be handled more easily because of developments in computational fluid dynamics (CFD) and finite element analysis (FEA) technologies. Furthermore, by providing accurate yet computationally economical approximations, the development of reduced-order models has helped close the gap between in-depth simulations and real-time applications [30]. Thermal modelling has evolved to account for the specific thermal properties of emerging materials, such as phase-change materials and high-conductivity composites. These developments are essential for addressing the increasing demands of high-performance and energy-efficient technologies, improving system reliability, and optimizing thermal performance [31].

V. COUPLED ELECTRICAL-THERMAL MODELS

A system's interrelated electrical and thermal characteristics are referred to as coupled electrical-thermal

dynamics. The performance, resistance, and general efficiency of electrical components are all impacted by the heat they produce while operating. On the other hand, variations in temperature have an impact on electrical characteristics including conductivity and carrier mobility. In energy systems, semiconductors, and high-power electronics, where accurate thermal control is essential to stability and failure prevention, this connection is especially significant. Since thermal and electrical behaviors are closely related in contemporary electrical systems, coupled electrical-thermal models are crucial for properly simulating and optimizing system performance. Heat is directly produced by electrical losses like copper and core losses, and this affects the electrical characteristics of components including insulation integrity, resistance, and magnetic permeability. To describe the reciprocal impacts of thermal and electrical processes, this dynamic interaction requires integrated modelling methodologies. Integrated modelling allows for accurate forecasts of system behavior under a range of operating situations by integrating thermal and electrical evaluations into a single framework. These methods are especially important for areas where compact designs and high-power densities worsen thermal issues, such as electric machines, power electronics, and renewable energy systems. Coupled models increase simulation accuracy and guide design choices by considering variables such transient heat generation, material characteristics, and cooling techniques [32]. Longer operational life, improved system efficiency, and improved thermal management are the outcomes of this. The need for integrated electrical-thermal modelling keeps increasing as companies strive for greater performance and energy efficiency, helped along by developments in multi-physics simulation technologies and computational tools.

Because of the intrinsic complexity and interconnection of these systems, coupled electrical-thermal models encounter several difficulties when merging the electrical and thermal domains. Resistivity, permeability, and heat transfer coefficients are examples of electrical and thermal characteristics that are strongly influenced by temperature [33]. Accurately capturing these nonlinear interactions calls for sophisticated modelling strategies and iterative computational approaches. Electrical systems encompass a wide range of operations, from macroscopic device behavior to microscopic material interactions. It might be computationally demanding to incorporate these multiscale effects into a connected model. It is crucial yet frequently unclear to define actual boundary conditions, such as cooling processes or thermal contact resistances, particularly in complex systems with dynamic working environments. Extensive experimental validation is necessary to ensure the accuracy of linked models, which can be resource-intensive and may require special setups to mimic real-world conditions. To overcome these obstacles, coupled electrical-thermal models for contemporary high-performance systems must be made more accurate, efficient, and useful by developments in computational, material science, and experimental approaches [34].

To improve the precision of performance forecasts and thermal control, coupled modelling approaches for Permanent Magnet Synchronous Motors (PMSMs) combine electrical and thermal assessments. To account for heat

generation from losses, such as copper, core, and stray losses, and their effects on motor components, a popular method combines thermal finite element analysis (FEA) with electromagnetic simulations [35]. To strike a compromise between accuracy and computing economy and enable real-time simulations for control system design, lumped parameter thermal models (LPMs) are frequently combined with comprehensive electromagnetic models. This integration is furthered by multi-physics simulation tools, which solve mechanical, thermal, and electromagnetic equations concurrently to capture the interdependencies between these domains. Computational fluid dynamics (CFD) and thermal models are used in advanced applications to optimize heat dissipation in PMSMs and assess cooling system efficiency [36]. These methods help the design of dependable, high-performance PMSMs for use such as renewable energy systems and electric vehicles by providing a thorough understanding of how heat affects magnetic characteristics, insulation integrity, and overall motor efficiency.

VI. KEY CHALLENGES IN ELECTRICAL AND THERMAL MODELING

When applied to real-world systems, electrical and thermal modelling presents several significant obstacles. In order to combine accuracy, scalability, and real-time practicality, addressing these difficulties calls for a combination of sophisticated computational tools, including upgraded material databases, reduced-order modelling, and adaptive algorithms.

A. The Intricacy of Implementing Real-Time control Systems

The computing demand and requirement for quick, precise predictions make it difficult to integrate coupled electrical and thermal models in real-time into control systems, such as those for motor drives or power converters. Although technically possible, simplified models may lose accuracy, particularly in dynamic operating environments [37].

B. Limitations of Material Properties and Parameter Identification

Precise understanding of material properties (such as resistivity and thermal conductivity) and loss mechanisms which might change with temperature and operating conditions are essential for accurate modelling [38]. It is frequently necessary to do lengthy testing or make assumptions to obtain these characteristics, which could result in mistakes.

C. Environmental Influences

Although they are frequently challenging to accurately estimate, external elements including ambient temperature, humidity, and cooling techniques (such as air or liquid cooling) have a substantial impact on thermal behavior. Uncertainties brought about by changes in the environment make forecasts and system optimization more difficult [39].

D. Scalability and Computational Cost

High-fidelity models, like coupled simulations based on CFD or finite elements, demand a large amount of processing

power [40]. It takes a lot of time and resources to scale these models for use in iterative design and optimization procedures or for larger or more complicated systems.

VII. ADVANCES AND INNOVATIONS IN MODELING TECHNIQUES

To handle complicated real-world applications, recent developments in modelling methodologies for electrical and thermal systems have concentrated on enhancing accuracy, efficiency, and predictive capabilities [41]. These developments are spurring innovation in a variety of sectors, but especially in fields where high-performance and energy-efficient solutions are essential, such as industrial automation, renewable energy, and electric cars.

A. New Developments in Model Accuracy and Efficiency

Advances in numerical approaches, like high-order finite element methods and adaptive meshing, have improved simulation accuracy while lowering processing overhead [42]. Because they provide a balance between speed and detail without compromising crucial dynamics, reduced-order models, or ROMs, have also become more popular for real-time applications.

B. Machine Learning and AI in Electrical and Thermal Predictions

By learning from massive datasets to spot trends and forecast results, machine learning (ML) and artificial intelligence (AI) are revolutionizing predictive modelling [43]. These techniques are especially useful for determining how a system will behave in different scenarios, maximizing design parameters, and allowing for real-time electrical and thermal performance monitoring in intricate systems.

C. Hybrid Modelling Techniques

To capitalize on the advantages of both data-driven and classic analytical models, hybrid approaches integrate them. For example, lumped parameter models that have been improved with machine learning methods may quickly and accurately forecast electrical and thermal behavior. Systems with complicated nonlinearities or partial data benefit greatly from such methods.

D. Digital Twins' Function in PMSM Drive Analysis

In PMSM drive analysis, digital twins' virtual copies of physical systems have become an extremely useful tool. Digital twins facilitate predictive maintenance, performance optimization, and dynamic monitoring by fusing high-fidelity coupled electrical-thermal models with real-time data [45]. Before they affect system performance, this method assists in identifying and resolving problems like overheating, demagnetization, or efficiency loss.

VIII. APPLICATIONS FOR ELECTRICAL AND THERMAL MODELING

The design and optimization of high-precision systems, especially in sectors where dependability, efficiency, and performance are crucial, depend on the use of electrical and thermal modelling. Advanced electrical and thermal modelling is essential for Permanent Magnet Synchronous Motors (PMSMs) in fields like industrial automation, robotics, aerospace, and electric vehicles (EVs) [46]. Precise

thermal modelling in robotics guarantees that small, powerful motors run effectively without overheating, even when loads fluctuate greatly. Coupled electrical-thermal models are used in aerospace, where harsh climatic conditions are common, to optimize cooling techniques and preserve system reliability while adhering to stringent weight and size restrictions.

The significance of these methods is demonstrated through case studies. For example, by combining finite element analysis and computational fluid dynamics to optimize cooling system designs, thermal management in EV motors has been enhanced, leading to longer motor life and increased energy efficiency. Hybrid modelling has also been used in aerospace systems to solve temperature issues in high-altitude motors, guaranteeing reliable operation in harsh circumstances. These illustrations highlight the ways in which sophisticated electrical and thermal modelling methods promote creativity and dependability in cutting-edge applications.

IX. FUTURE RESEARCH DIRECTIONS

Electrical and thermal modeling is in a strong position to manage future opportunities and challenges in high-performance systems thanks to the application of innovative techniques and new materials. There are several opportunities to enhance the coupling of the electrical and thermal domains by incorporating more complex interactions, such as localized heating effects on magnetic properties or transient thermal impacts on electrical efficiency. Fully integrated models may be better able to manage complex conditions such as dynamic load variations or fault events [47]. Dynamic optimization and adaptive control strategies may be made possible by extending multi-physics methodologies to incorporate mechanical, thermal, and electromagnetic interactions in real-time simulations. This would have a significant effect on applications where quick reaction and effective operation are essential, such as electric cars and renewable energy systems. There are chances to greatly enhance heat dissipation through research into cutting-edge materials including phase-change materials, high-conductivity composites, and nanostructured heat sinks. In a similar vein, better winding insulation and low-loss magnetic materials may increase thermal performance and lower electrical losses.

The advancement of parallel processing methods and high-performance computing (HPC) will make it possible to model large-scale, high-power PMSM systems more quickly and precisely. For industrial and transportation applications, this will enable more precise design, performance optimization, and failure prediction. Future research will help technological developments like driverless vehicles, renewable energy integration, and next-generation manufacturing by tackling these directions and resulting in more sustainable, dependable, and efficient electrical systems [48].

X. DISCUSSION

The increasing complexity of contemporary motor systems and the significance of reliable, integrated modelling methodologies are highlighted by the difficulties and developments in electrical and thermal modelling for high-

precision Permanent Magnet Synchronous Motor (PMSM) drives [49]. To effectively mimic PMSM behavior, complex methodologies are required because of the bidirectional link between electrical losses and thermal effects. Although computational fluid dynamics (CFD) and finite element analysis (FEA) provide high-fidelity solutions, real-time applications are frequently constrained by their computing requirements. This gap is filled by simplified methods, such as lumped parameter models, but at the expense of decreased precision. One crucial area for improvement is striking a balance between computing efficiency and accuracy. The integration of machine learning and hybrid modeling techniques has shown significant promise in addressing nonlinearities and uncertainties in PMSM systems. Innovations in materials science, such as advanced magnetic materials and high-conductivity composites, further aid in reducing losses and improving thermal performance. These advancements not only enhance motor efficiency but also pave the way for more compact and high-power designs suitable for demanding applications.

For high-precision applications like robotics, aerospace, electric vehicles, and industrial automation, precise electrical and thermal models are essential. In these domains, it is crucial to anticipate and avoid issues such as demagnetization, heat hotspots, or efficiency losses [50]. Case examples that demonstrate how advanced modeling techniques have improved system performance and dependability in different fields serve to further highlight the importance of continuous innovation. More integration of multi-physics simulation approaches is required, particularly to address real-time control challenges. Another crucial avenue is the investigation of new materials for enhanced heat control and loss mitigation. Scaling these solutions for bigger, more complicated systems will require advances in computational capabilities, such as reduced-order models and parallel processing. The conversation concludes by exposing a dynamic environment where ground-breaking inventions and difficulties in electrical and thermal modelling converge. Meeting the changing needs of high-precision PMSM drives, and their applications will require sustained attention to developing innovative materials, improving computing efficiency, and integrating emerging technologies.

XI. CONCLUSION

To meet the increasing demands for efficiency, reliability, and performance, high-precision Permanent Magnet Synchronous Motor (PMSM) drives require sophisticated modelling methodologies due to the complex interaction between electrical and thermal processes. This paper emphasizes the difficulties in combining the electrical and thermal domains, such as computing limitations, environmental effects, parameter uncertainty, and the difficulty of real-time implementation. However, new developments in modelling techniques, including hybrid approaches, multi-physics simulations, and the use of AI and machine learning, present encouraging answers to these problems. Although modern approaches like artificial intelligence (AI) and digital twins provide substantial improvements, they also have drawbacks. Large, high-quality datasets are necessary for training AI models, but they are not always accessible, which could result in biases or erroneous

predictions. PMSM system design and operation are further improved using digital twins in conjunction with innovative materials for heat dissipation and loss reduction. To optimize large-scale systems and handle new applications in robotics, aerospace, electric cars, and industrial automation, future research must concentrate on a deeper integration of electrical and thermal models, utilizing advances in computer power and novel materials. The industry may make revolutionary advancements in PMSM technology by filling existing gaps and increasing modelling precision, opening the door for future high-performance and sustainable systems.

REFERENCES

- [1] B. Su, X. Sun, L. Chen, Z. Yang, and K. Li, "Thermal modeling and analysis of bearingless permanent magnet synchronous motors," *International Journal of Applied Electromagnetics and Mechanics*, vol. 56, no. 1, pp. 115-130, 2018, <https://doi.org/10.3233/JAE-170112>.
- [2] Y. Zhang, D. Xu, J. Liu, S. Gao and W. Xu, "Performance Improvement of Model-Predictive Current Control of Permanent Magnet Synchronous Motor Drives," *IEEE Transactions on Industry Applications*, vol. 53, no. 4, pp. 3683-3695, 2017, <https://doi.org/10.1109/TIA.2017.2690998>.
- [3] S. Mukundan, H. Dhulipati, J. Tjong and N. C. Kar, "Parameter Determination of PMSM Using Coupled Electromagnetic and Thermal Model Incorporating Current Harmonics," *IEEE Transactions on Magnetics*, vol. 54, no. 11, pp. 1-5, 2018, <https://doi.org/10.1109/TMAG.2018.2837087>.
- [4] U. Abubakar, X. Wang, S. H. Shah, L. Wang, and A. Farouk, "Electromagnetic and thermal analysis of 225 kW high-speed PMSM for centrifugal blower applications," *Energies*, vol. 15, no. 9, p. 3370, 2022, <https://doi.org/10.3390/en15093370>.
- [5] S. Amami, Z. Souissi and A. Messaoud, "Temperature Prediction for PMSM Motors Using Deep Learning Algorithms," *2024 IEEE International Multi-Conference on Smart Systems & Green Process (IMC-SSGP)*, pp. 1-5, 2024, <https://doi.org/10.1109/IMC-SSGP63352.2024.10919684>.
- [6] T. Dong, X. Zhang, C. Zhu, F. Zhou and Z. Sun, "Improved Thermal Modeling Methodology for Embedded Real-Time Thermal Management System of Automotive Electric Machines," *IEEE Transactions on Industrial Informatics*, vol. 17, no. 7, pp. 4702-4713, 2021, <https://doi.org/10.1109/TII.2020.3004389>.
- [7] Y. Duan and D. M. Ionel, "A Review of Recent Developments in Electrical Machine Design Optimization Methods With a Permanent-Magnet Synchronous Motor Benchmark Study," *IEEE Transactions on Industry Applications*, vol. 49, no. 3, pp. 1268-1275, 2013, <https://doi.org/10.1109/TIA.2013.2252597>.
- [8] M. Jia, J. Hu, F. Xiao, Y. Yang, and C. Deng, "Modeling and analysis of electromagnetic field and temperature field of permanent-magnet synchronous motor for automobiles," *Electronics*, vol. 10, no. 17, p. 2173, 2021, <https://doi.org/10.3390/electronics10172173>.
- [9] S. Khalesidoost, J. Faiz, and E. Mazaheri-Tehrani, "An overview of thermal modelling techniques for permanent magnet machines," *IET Science, Measurement & Technology*, vol. 16, no. 4, pp. 219-241, 2022, <https://doi.org/10.1049/smt2.12099>.
- [10] D. Bobba *et al.*, "Multi-Physics Based Analysis and Design of Stator Coil in High Power Density PMSM for Aircraft Propulsion Applications," *2021 AIAA/IEEE Electric Aircraft Technologies Symposium (EATS)*, pp. 1-9, 2021, <https://doi.org/10.23919/EATS52162.2021.9704820>.
- [11] T. Song, H. Liu, Q. Zhang, and Z. Zhang, "Multi-physics and multi-objective optimisation design of interior permanent magnet synchronous motor for electric vehicles," *IET Electric Power Applications*, vol. 14, no. 11, pp. 2243-2254, 2020, <https://doi.org/10.1049/iet-epa.2020.0136>.
- [12] M. A. Azom, M. S. Hossain, and M. Y. A. Khan, "Review of Electrical and Thermal Modeling Techniques for Three-Phase PMSM Drives," *Control Systems and Optimization Letters*, vol. 3, no. 1, pp. 75-83, 2025, <https://doi.org/10.59247/csol.v3i1.172>.
- [13] G. D. Demetriades, H. Z. de la Parra, E. Andersson and H. Olsson, "A Real-Time Thermal Model of a Permanent-Magnet Synchronous Motor," *IEEE Transactions on Power Electronics*, vol. 25, no. 2, pp. 463-474, 2010, <https://doi.org/10.1109/TPEL.2009.2027905>.
- [14] A. Ranjan, D. V. Bhaskar, P. Kumar and U. R. Muduli, "Comprehensive Analysis of Thermal Effects on PMSM Drive Control in Small Commercial Vehicles," *2024 IEEE International Conference on Power Electronics, Drives and Energy Systems (PEDES)*, pp. 1-6, 2024, <https://doi.org/10.1109/PEDES61459.2024.10961171>.
- [15] X. Xu *et al.*, "Heat dissipation design and performance optimization of high speed train PMSM based on coupled electromagnetic-thermal field," *Case Studies in Thermal Engineering*, vol. 61, p. 104904, 2024, <https://doi.org/10.1016/j.csite.2024.104904>.
- [16] Z. Zhang, Q. Song, and B. Ahmed, "Optimized flow rate and efficient shaft water cooling method for EV's PMSM temperature-dependent energy system output power increase," *Case Studies in Thermal Engineering*, vol. 61, p. 104901, 2024, <https://doi.org/10.1016/j.csite.2024.104901>.
- [17] H. Bai, Q. Li, H. Luo, Y. Huangfu and F. Gao, "Nonlinear Behavioral Modeling and Real-Time Simulation of Electric Propulsion System for the High-Fidelity X-in-the-Loop Applications," *IEEE Transactions on Transportation Electrification*, vol. 9, no. 1, pp. 1708-1722, 2023, <https://doi.org/10.1109/TTE.2022.3192872>.
- [18] W. Tong, R. Sun, S. Li and R. Tang, "Loss and Thermal Analysis for High-Speed Amorphous Metal PMSMs Using 3-D Electromagnetic-thermal Bi-Directional Coupling," *IEEE Transactions on Energy Conversion*, vol. 36, no. 4, pp. 2839-2849, 2021, <https://doi.org/10.1109/TEC.2021.3065336>.
- [19] L. Liu, W. N. Fu, S. Yang and S. L. Ho, "Iron Loss Separation in High Frequency Using Numerical Techniques," *IEEE Transactions on Magnetics*, vol. 52, no. 3, pp. 1-4, 2016, <https://doi.org/10.1109/TMAG.2015.2498203>.
- [20] E. Gundabattini, A. Mystkowski, A. Idzkowski, and D. G. Solomon, "Thermal mapping of a high-speed electric motor used for traction applications and analysis of various cooling methods—A review," *Energies*, vol. 14, no. 5, p. 1472, 2021, <https://doi.org/10.3390/en14051472>.
- [21] H. Li, X. Zhang, S. Yang and S. Liu, "Unified Graphical Model of High-Frequency Signal Injection Methods for PMSM Sensorless Control," *IEEE Transactions on Industrial Electronics*, vol. 67, no. 6, pp. 4411-4421, 2020, <https://doi.org/10.1109/TIE.2019.2924863>.
- [22] M. Al-Gabalawy, A. H. Elmetwaly, R. A. Younis, and A. I. Omar, "Temperature prediction for electric vehicles of permanent magnet synchronous motor using robust machine learning tools," *Journal of Ambient Intelligence and Humanized Computing*, vol. 15, no. 1, pp. 243-260, 2024, <https://doi.org/10.1007/s12652-022-03888-9>.
- [23] C. Paar, A. Muetze and H. Kolbe, "Influence of Machine Integration on the Thermal Behavior of a PM Drive for Hybrid Electric Traction," *IEEE Transactions on Industry Applications*, vol. 51, no. 5, pp. 3914-3922, 2015, <https://doi.org/10.1109/TIA.2015.2427280>.
- [24] S. -W. Hwang, J. -W. Chin and M. -S. Lim, "Design Process and Verification of SPMSM for a Wearable Robot Considering Thermal Characteristics Through LPTN," *IEEE/ASME Transactions on Mechatronics*, vol. 26, no. 2, pp. 1033-1042, 2021, <https://doi.org/10.1109/TMECH.2020.3015561>.
- [25] Z. Song and C. Liu, "Energy efficient design and implementation of electric machines in air transport propulsion system," *Applied Energy*, vol. 322, p. 119472, 2022, <https://doi.org/10.1016/j.apenergy.2022.119472>.
- [26] M. Zhu, W. Hu and N. C. Kar, "Acoustic Noise-Based Uniform Permanent-Magnet Demagnetization Detection in SPMSM for High-Performance PMSM Drive," *IEEE Transactions on Transportation Electrification*, vol. 4, no. 1, pp. 303-313, 2018, <https://doi.org/10.1109/TTE.2017.2755549>.
- [27] J. Ji, Y. Yang, Z. Ling and W. Zhao, "Multi-Objective Optimization of Interior Permanent Magnet Machine for Heavy-Duty Vehicle Direct-Drive Applications," *IEEE Transactions on Energy Conversion*, vol. 37, no. 3, pp. 1946-1954, 2022, <https://doi.org/10.1109/TEC.2022.3155160>.
- [28] M. Y. A. Khan, "A Review of Analysis and Existing Simulation Model of Three Phase Permanent Magnet Synchronous Motor Drive (PMSM)," *Control Systems and Optimization Letters*, vol. 2, no. 3, pp. 349-356, 2024, <https://doi.org/10.59247/csol.v2i3.151>.

- [29] Z. Huang, F. J. Márquez-Fernández, Y. Loayza, A. Reinap and M. Alaküla, "Dynamic thermal modeling and application of electrical machine in hybrid drives," *2014 International Conference on Electrical Machines (ICEM)*, pp. 2158-2164, 2014, <https://doi.org/10.1109/ICELMACH.2014.6960483>.
- [30] S. Madhavan, R. D. PB, E. Gundabattini, and A. Mystkowski, "Thermal analysis and heat management strategies for an induction motor, a review," *Energies*, vol. 15, no. 21, p. 8127, 2022, <https://doi.org/10.3390/en15218127>.
- [31] G. Puccio, M. Raimondo, S. Nategh, D. Barater, D. Ericsson and A. Carlsson, "An Advanced Thermal Modeling Method for Directly Oil-cooled Traction Motors," *2023 IEEE Workshop on Electrical Machines Design, Control and Diagnosis (WEMDCD)*, pp. 1-6, 2023, <https://doi.org/10.1109/WEMDCD55819.2023.10110946>.
- [32] Y. Li, T. Lin, R. Mai, L. Huang and Z. He, "Compact Double-Sided Decoupled Coils-Based WPT Systems for High-Power Applications: Analysis, Design, and Experimental Verification," *IEEE Transactions on Transportation Electrification*, vol. 4, no. 1, pp. 64-75, 2018, <https://doi.org/10.1109/TTE.2017.2745681>.
- [33] S. Mukundan, H. Dhulipati, J. Tjong and N. C. Kar, "Parameter Determination of PMSM Using Coupled Electromagnetic and Thermal Model Incorporating Current Harmonics," *IEEE Transactions on Magnetics*, vol. 54, no. 11, pp. 1-5, 2018, <https://doi.org/10.1109/TMAG.2018.2837087>.
- [34] Z. Xu, Y. Xu, Y. Gai and W. Liu, "Thermal Management of Drive Motor for Transportation: Analysis Methods, Key Factors in Thermal Analysis, and Cooling Methods—A Review," *IEEE Transactions on Transportation Electrification*, vol. 9, no. 3, pp. 4751-4774, 2023, <https://doi.org/10.1109/TTE.2023.3244907>.
- [35] J. Han, H. Shu, X. Tang, X. Lin, C. Liu, and X. Hu, "Predictive energy management for plug-in hybrid electric vehicles considering electric motor thermal dynamics," *Energy Conversion and Management*, vol. 251, p. 115022, 2022, <https://doi.org/10.1016/j.enconman.2021.115022>.
- [36] T. Krainer, D. Wöckinger, G. Bramerdorfer and S. Chukwulobe, "Hybrid Thermal Network Identification for Sensorless Temperature Monitoring of a PMSM Considering Speed-Dependent Cooling Effects," *2024 IEEE Energy Conversion Congress and Exposition (ECCE)*, pp. 5690-5697, 2024, <https://doi.org/10.1109/ECCE55643.2024.10860841>.
- [37] L. Wang, Y. Li, F. Marignetti and A. Boglietti, "Coupled Fluid-Solid Heat Transfer of A Gas and Liquid Cooling PMSM Including Rotor Rotation," *IEEE Transactions on Energy Conversion*, vol. 37, no. 1, pp. 443-453, 2022, <https://doi.org/10.1109/TEC.2021.3087831>.
- [38] M. Karamuk, "Review of Electric Vehicle Powertrain Technologies with OEM Perspective," *2019 International Aegean Conference on Electrical Machines and Power Electronics (ACEMP) & 2019 International Conference on Optimization of Electrical and Electronic Equipment (OPTIM)*, 2019, <https://doi.org/10.1109/ACEMP-OPTIM44294.2019.9007175>.
- [39] W. Zhao, X. Wang, C. Gerada, H. Zhang, C. Liu and Y. Wang, "Multi-Physics and Multi-Objective Optimization of a High Speed PMSM for High Performance Applications," *IEEE Transactions on Magnetics*, vol. 54, no. 11, pp. 1-5, 2018, <https://doi.org/10.1109/TMAG.2018.2835504>.
- [40] K. Zhou, J. Pries and H. Hofmann, "Computationally Efficient 3-D Finite-Element-Based Dynamic Thermal Models of Electric Machines," *IEEE Transactions on Transportation Electrification*, vol. 1, no. 2, pp. 138-149, 2015, <https://doi.org/10.1109/TTE.2015.2456429>.
- [41] X. Zhang, L. Yang, X. Sun, Z. Jin and M. Xue, "A Predictive PMP Strategy for Plug-In Hybrid Electric Buses Considering Motor Thermal Characteristics and Loss Distribution," *IEEE Transactions on Transportation Electrification*, vol. 10, no. 1, pp. 1982-1994, 2024, <https://doi.org/10.1109/TTE.2023.3288868>.
- [42] P. Tang, Z. Zhao, and H. Li, "Transient Temperature Field Prediction of PMSM Based on Electromagnetic-Heat-Flow Multi-Physics Coupling and Data-Driven Fusion Modeling," *SAE International Journal of Advances and Current Practices in Mobility*, vol. 6, no. 2023-01-7031, pp. 2379-2389, 2023, <https://doi.org/10.4271/2023-01-7031>.
- [43] M. A. Azom and M. Y. A. Khan, "Recent Developments in Control and Simulation of Permanent Magnet Synchronous Motor Systems," *Control Systems and Optimization Letters*, vol. 3, no. 1, pp. 84-91, 2025, <https://doi.org/10.59247/csol.v3i1.173>.
- [44] M. Y. A. Khan, "Enhancing Electric Vehicle Performance: A Case Study on Advanced Motor Drive Systems, Integration, Efficiency, and Thermal Management," *Control Systems and Optimization Letters*, vol. 3, no. 1, pp. 20-27, 2025, <https://doi.org/10.59247/csol.v3i1.152>.
- [45] P. Roy, M. Towhidi, F. Ahmed, S. Mukundan, H. Dhulipati, and N. Kar, "A novel hybrid technique for thermal analysis of permanent magnet synchronous motor used in electric vehicle application," 2020, <https://doi.org/10.4271/2020-01-0464>.
- [46] P. Zhou, Y. Xu and F. Xin, "Study of Magneto-Thermal Problems in Low-Speed High-Torque Direct Drive PMSM Based on Demagnetization Detection and Loss Optimization of Permanent Magnets," *IEEE Access*, vol. 11, pp. 92055-92069, 2023, <https://doi.org/10.1109/ACCESS.2023.3306952>.
- [47] J. Dong, Y. Huang, L. Jin, H. Lin and H. Yang, "Thermal Optimization of a High-Speed Permanent Magnet Motor," *IEEE Transactions on Magnetics*, vol. 50, no. 2, pp. 749-752, 2014, <https://doi.org/10.1109/TMAG.2013.2285017>.
- [48] L. Bin, Y. Zhongjun and F. Jia, "Thermal Modeling and Analysis of a HPMSM Coupling With Magnetic Bearings," *IEEE Access*, vol. 12, pp. 81362-81373, 2024, <https://doi.org/10.1109/ACCESS.2024.3410326>.
- [49] M. N. Hussain, M. A. Halim, M. Y. A. Khan, S. Ibrahim, and A. Haque, "A comprehensive review on techniques and challenges of energy harvesting from distributed renewable energy sources for wireless sensor networks," *Control Systems and Optimization Letters*, vol. 2, no. 1, pp. 15-22, 2024, <https://doi.org/10.59247/csol.v2i1.60>.
- [50] S. C. Carpiuc and C. Lazar, "Modeling of synchronous electric machines for real-time simulation and automotive applications," *Journal of the Franklin Institute*, vol. 354, no. 14, pp. 6258-6281, 2017, <https://doi.org/10.1016/j.franklin.2017.07.030>.